

Care & Maintenance

TIMBER FLOORING AND DECKING



Care and maintenance

TIMBER FLOORING

A hardwood timber floor represents a long-term investment and with regular cleaning and maintenance, a timber floor can look beautiful for a lifetime. Timber floors are easy to clean and maintain by following a few easy guidelines.

General precautions and maintenance tips

- Dirt and grit can lead to excess wear and scratching
 of a hardwood timber floor. Use dirt trapping mats at all
 exterior doors to minimise dirt, sand and grit that might be
 brought inside. Small rugs and hall runners are also helpful
 for collecting dirt that can scratch a hardwood timber floor.
 Regularly sweep high traffic areas with a soft bristle broom
 or electrostatic mop.
- Fit protective pads to furniture legs to reduce risk of scuffing the floor when moved. To protect the floor surface use protective mats for furniture with castors. Barrel castors are less likely to damage a floor than ball castors.
- In areas where extreme temperature changes or moisture variation are common, gaps or cupping may appear in the floor. Maintain an ambient temperature to avoid dryness that may cause gaps, or moisture increases that may cause cupping.
- All hardwood timber floors will fade, darken or change shade over time. Exposure to sunlight will increase this process.
 Rotate rugs periodically and protect the floor from direct sunlight with curtains or blinds.
- High heel shoes can dent a hard floor surface. Remove shoes that have exposed heels with sharp points to avoid potential damage to a hardwood timber floor.
- Pets with long nails or claws can scratch and dull the floor finish, make sure pets nails or claws are trimmed regularly and kept blunt.
- One of the benefits of a hardwood timber floor is that it can be refinished if it becomes excessively scratched or dented. Boral Timber recommends the use of a qualified flooring professional proficient in sanding and finishing to complete this work.

The beauty of hardwood timber from Boral Timber For generations, the distinctive beauty of hardwood timber has brought warmth and elegance to Australian homes, both inside and out. Boral Timber's hardwood products offer unique colours and grains to create a stunning feature. Hardwoods are also ideal for commercial or domestic developments due to their natural hardness.

Cleaning tips

- A hardwood timber floor will look better for longer if it is kept as clean as possible. To remove surface dirt and grit, regularly vacuum, with a soft bristle head or an electrostatic attachment, or sweep with an electrostatic mop. Keep door mats clean.
- For stubborn dirt, damp-mop the floor using a well rung mop. The use of a pH neutral floor cleaner can help remove stubborn dirt (use as per manufacturer's instructions).
- Never clean a floor with common household detergents, polishes, steel wool pads, wax or similar products.
 These products can be too abrasive and scratch the surface, or may make a floor dangerously slippery.
 Some products may leave a film of silicon or wax on the timber which may hamper recoating of your floor in the future. Never use Methylated Spirits or Kerosene, as any type of petroleum distillate will degrade the coating and irreversibly dull the floor. Only use a pH neutral floor cleaner as per manufacturer's instructions.
- Boral Timber has a range of floor cleaning and maintenance products available. Contact 1800 818 317 for further information.
- Use only quality lint free floor mops and thoroughly wash new mops to remove any lint.
- Wipe up spills and leaks promptly with a dry cloth or dry paper towel. For sticky substances, moisten the cloth slightly.
- Boral Timber uses sophisticated processing technology for all kiln dried timber and rigorous floor placement procedures to control the moisture content. Over wetting a floor when mopping or cleaning can change the moisture balance and cause a floor to expand, with some resulting in cupping.
 For this reason, it is important to ensure that mops and cloths are well wrung so that as little water solution as possible wets the floor.
- Steam mops are not recommended for cleaning timber floors. Steam (moisture) is forced into the joints of the timber and any small, breaks or cracks on the timber floor surface which could result in unusual reactions in the timber such as cupping. The heat from the steam mop could also cause damaged to the coating on the floor.

DECKING

In order to keep a hardwood timber deck looking its best, it must be kept clean and well maintained. It is a good idea to inspect a hardwood timber deck at least annually to ensure that it is in good condition.

The deck must be regularly maintained as it may become discoloured or affected by moisture and weather. Inspect the deck to replace loose boards and protruding nails or screws. Any loose or damaged boards should be resecured or replaced, loose nails hammered back in or screws refixed.

To clean the deck, sweep off any loose dirt or garden residue and then clean the deck with a specialised deck cleaning product. It is important to not only remove dirt, but any algae or moss that may be growing on the deck. After the cleaning has been completed, lightly sand the deck in the direction of the timber. This will remove any splinters and damage to the timber.

Once cleaned, reseal the deck with a stain, oil, paint or varnish, depending on aesthetic preference. Before the decking finish is applied, cover areas around the deck that need protection such as plants and furniture. Drying times are dependent on the type of finish so check finish manufacturer's recommendations before walking on a newly finished deck. Apply and re-apply decking finish as per finish manufacturer's recommendations. Finish manufacturers may recommend that the decking finish needs to be re-applied more than once a year.

After a new timber deck has been built, or an existing deck repaired, thoroughly sweep and clean to remove metal filings from drilling, nailing or other construction materials that may cause black spots on the hardwood deck when exposed to the elements.

If the deck has turned grey from natural weathering or is discoloured due to metal filings or other construction materials, there are a large range of maintenance and cleaning products on the market which can bring back the timber's original colour. Use with care and follow the finish manufacturer's instructions carefully.



For full installation, care and maintenance or warranty information, please contact Boral Timber on 1800 818 317 or visit www.boral.com.au/timber



notice in accordance with its policy of continued product development.

Every care has been taken in preparing the information contained in this publication, however the company cannot accept responsibility for any inaccuracies that may have arisen and cannot accept liability for loss or damage either direct or consequential arising out of or in relation to use of application of the said information.

Printed on recycled paper using vegetable inks

Boral® and Build something great™ are registered trade marks of Boral Limited or one of it's subsidiaries.

www.boral.com.au/timber
National free call 1800 818 317

